



Rm. 408, Building 1, No. 31, Yinshan Road  
Yuelu District, Changsha, Hunan 410013  
People's Republic of China

Tel: +86-13636523212  
Email: sales@aemproduct.com  
Web: www.aemproduct.com

Current Version: 1.0  
Revision Date: Apr 19, 2016

## Material Safety Data Sheet

Identity: Indium Selenide

Formula: In<sub>2</sub>Se<sub>3</sub>

### SECTION I - GENERAL INFORMATION

Manufacturer: Advanced Engineering Materials Limited (AEM)

The information below is believed to be accurate and represents the best information available to AEM. However, AEM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

### SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

CAS #	OSHA PEL	ACGIH TLV	%
12056-07-4	NE	0.1 mg /m <sup>3</sup>	0.0-100.0%

### SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: N/A

Vapor Pressure (vs. air or mmHg): N/A

Melting Point: 890°C

Specific Gravity (Water=1): 5.67 gm/cc at 25.0°C (77.0°F)

Evaporation Rate: N/A

Flash Point: N/A

Solubility in water: NE

*Appearance and odor:* Black powder and pieces, no odor.

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

*Method Used:* None-flammable

*Explosive Limits:* LEL: N/A

UEL: N/A

*Extinguishing Media:* Use suitable extinguishing agent for surrounding material and type of fire

*Special Fire Fighting Procedures:*

Firefighters must wear full face, self-contained breathing apparatus and full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

*Unusual Fire and Explosion Hazards:*

When heated to decomposition, indium selenide may emit fumes of selenium.



Rm. 408, Building 1, No. 31, Yinshan Road  
Yuelu District, Changsha, Hunan 410013  
People's Republic of China

Tel: +86-13636523212  
Email: sales@aemproduct.com  
Web: www.aemproduct.com

## SECTION V - REACTIVITY DATA

*Stability:* Stable

*Conditions to Avoid (instability):* None

*Incompatibility:* None recorded

*Hazardous Decomposition or Byproducts:* Fumes of selenium

*Hazardous Polymerization:* Will not occur.

*Conditions to avoid (hazardous polymerization):* None.

## SECTION VI - HEALTH HAZARD DATA

*Routes of entry:* Inhalation? Yes      Skin? Yes      Eyes? Yes

Ingestion? Yes      Other? No

To the best of our knowledge the chemical, physical and toxicological properties of antimony sulfide have not been thoroughly investigated and recorded.

Selenium compounds are poison by inhalation and intravenous routes. Some selenium compounds are experimental carcinogens. Long-term exposure may be a cause of amyotrophic lateral sclerosis in humans, just as it may cause "blind staggers" in cattle. Elemental selenium has low acute systemic toxicity, but dust or fumes can cause serious irritation of the respiratory tract. Inorganic selenium compounds can cause dermatitis. Garlic odor of breath is a common symptom. Pallor, nervousness, depression, digestive disturbances and death have been reported in cases if chronic exposure. (Sax, Dangerous Properties of Industrial Materials, eighth edition)

### Signs and Symptoms of Overexposure:

*Inhalation:* Acute selenium poisoning may cause: nervousness, fever, vomiting, somnolence, drop in blood pressure, labored breathing and toxic action on the nervous system may lead to respiratory failure.

Chronic selenium poisoning may cause: depression, marked pallor, coated tongue, gastrointestinal disorders, garlic odor of the breath.

*Ingestion:* Chronic selenium poisoning may cause: alkali disease, loss of vitality, lameness, atrophy, cirrhosis of the liver, degeneration and necrosis of the myocardium.

*Skin:* May cause redness, itching, inflammation, burning sensation and swelling.

*Eye:* May cause redness, itching, burning and watering.

### Health Hazards (Acute and Chronic):

*Inhalation:*

Acute: DANGER-POISON. May cause acute selenium poisoning and irritation to the respiratory tract.

Chronic: May cause pneumonitis and chronic selenium poisoning. Continued intoxication may cause loss of nails and hair, hemolytic anemia, kidney, liver and spleen damage.



Rm. 408, Building 1, No. 31, Yinshan Road  
Yuelu District, Changsha, Hunan 410013  
People's Republic of China

Tel: +86-13636523212  
Email: sales@aemproduct.com  
Web: www.aemproduct.com

---

*Ingestion:*

Acute: DANGER-POISON. May cause irritation to the gastrointestinal tract.

Chronic: May cause chronic selenium toxicity.

*Skin:*

Acute: May cause irritation.

Chronic: May cause dermatitis.

*Eye:*

Acute: May cause irritation to the conjunctiva.

Chronic: No chronic health effects recorded.

*Target Organs:* May affect the respiratory system, skin, liver, blood and kidneys.

*Carcinogenicity:* NTP? No      IARC Monographs? No      OSHA Regulated? No

*Medical Conditions Aggravated by Exposure:* Pre-existing respiratory and gastric disorders.

*Emergency and First Aid Procedures:*

*Inhalation:* Remove victim to fresh air; keep warm and quiet; give oxygen if breathing is difficult and seek medical attention.

*Ingestion:* Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person.

*Skin:* Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist.

*Eye:* Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE
---

*Steps to be taken in case material is released or spilled:*

Wear appropriate respiratory and protective equipment. Isolate spill area and provide ventilation. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

*Waste disposal method:*

Dispose of in accordance with state, local, and federal regulations.

*Hazard Label Information:*

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

SECTION VIII - CONTROL MEASURES
---------------------------------



# Advanced Engineering Materials

Rm. 408, Building 1, No. 31, Yinshan Road  
Yuelu District, Changsha, Hunan 410013  
People's Republic of China

Tel: +86-13636523212  
Email: [sales@aemproduct.com](mailto:sales@aemproduct.com)  
Web: [www.aemproduct.com](http://www.aemproduct.com)

---

*Protective Equipment Summary (Hazard Label Information):*

NIOSH approved respirator, impervious gloves, safety glasses, clothes to prevent contact.

*Ventilation:*

Local Exhaust: To maintain concentration at low exposure levels.

Special: Handle in a controlled enclosed environment.

Mechanical (General): Good general ventilation is recommended.

*Work/Hygienic/Maintenance Practices:*

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established
---